

# REDROCK LTD.

## Material Safety Data Sheet

<b>1) PRODUCT NAME</b>	<b>ECOFINE 500</b>
General Description:	Mould Release Agent
Red Rock (2004) Ltd. PO Box 12091 Birmingham B13 9EL	
Tel: (0044) 0870 910 7799 Fax: (0044) 0121 246 4441 Email: info@redrock-uk.co.uk	
<b>2) COMPOSITION / INFORMATION ON INGREDIENTS:</b>	
Blend of fatty acid esters.	
<b>3) HAZARDS IDENTIFICATION:</b>	
Classed as low hazard. Prolonged contact with unprotected skin may cause irritation Spillages are a slip hazard and should be cleaned up immediately.	
<b>4) FIRST AID MEASURES</b>	
Skin:	Remove contaminated clothing. Wash off with water.
Eyes:	Flush eyes with flowing water for at least 10 minutes.
Ingestion:	Rinse mouth with water. Drink 1 – 2 glasses of water.
Inhalation:	Remove to fresh air.
Other information:	The above actions are those required for any product which does not have any special medical effects. Contaminated clothing should be washed before re-use.
<b>5) FIRE FIGHTING MEASURES:</b>	
The product does not constitute a fire hazard. However, water mist, foam, carbon dioxide, dry powder are all suitable extinguishing media for fire involving Ecofine 500	
<b>6) ACCIDENTAL RELEASE MEASURES</b>	
Spillages should be contained by and covered with sand, earth, or similar absorbent material as vermiculite. The mixture can then be shovelled into containers. The area can then be cleaned with water.	
MSDS reference: RRK ECO 500 - 02/05    Material: Ecofine 500    Page 1/3	

## 7) HANDLING AND STORAGE:

Store in sealed containers under ambient conditions, ideally between 5C and 25C. Protect from frost.

## 8) EXPOSURE CONTROLS / PERSONAL PROTECTION:

Personal protective equipment: The product is classified low hazard to health, however if there is the possibility of prolonged contact with skin it is recommended that overalls and protective gloves be worn.

If the product is to be spray applied then eye protection would also be advised.

Personal exposure limits: No assigned exposure limits by any Regulatory Authority

## 9) PHYSICAL AND TECHNICAL SAFETY DATA

Appearance:	Yellow liquid (20C)
Boiling/Melting/Freezing:	Boiling Point > 300 deg C. Freezing Point > -15deg C
Specific Gravity/Bulk Density	SG ca. 0.875
Vapour Pressure:	Not determined
Viscosity:	ca. 10 mPas (20 deg C)
Solubility:	immiscible in water
PH	not applicable
Flash Point	>180 deg C
Ignition temperature	Not determined
Explosive Limits	Not determined
Other Information:	

## 10) STABILITY AND REACTIVITY:

Thermal decomposition:	Not determined.
Hazardous Decomposition Products:	Oxides of carbon.
Hazardous reactions:	Avoid strong oxidising agents as for any organic chemical.

## 11) TOXICOLOGICAL INFORMATION:

Acute oral toxicity LD50= >2000mg/kg. (OECD401).

## 12) ECOLOGICAL INFORMATION

The product is considered to be readily biodegradable (OECD 301 A-F) based on data obtained for similar compounds.

## 13) DISPOSAL CONSIDERATIONS:

Waste product must be disposed of according to the Duty of Care regulations.

## 14) TRANSPORT REGULATIONS:

UN Number:

ICAO- Air:

IMO-Sea:

ADR-Road:

CDG-Road:

Proper Shipping Name:

Additional Data: The product is classified low hazard according to these regulations.

## 15) REGULATORY INFORMATION:

Labelling: The product is classified low hazard for labelling purposes according to UK and EC regulations

Other: The product is listed on the European Inventory of Existing Chemical Substances.

## 16) FURTHER INFORMATION

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our product from the point of view of safety requirements and is not intended to guarantee any particular properties.

MSDS reference:: RRK ECO 500 - 02/05

Material: Ecofine 500 Page 3 /3

Registered Office:

Red Rock (2004) Ltd, Croft House, Station Rd. BARNOLDSWICK, Lancs, UK. BB18 5NA

Registered number : 3981500 England and Wales